



Overview

Model Name	APC Back-UPS 650VA Standby with Schuko
Includes	CD with software , USB cable , User Manual
Standard Lead Time	Usually in Stock
Product Distribution	Armenia , Azerbaijan , Belarus , Georgia , Kazakhstan , Moldova, Republic Of , Mongolia , Russian Federation , Tajikistan , Turkmenistan , Ukraine , Uzbekistan

Output

Output Power Capacity	390 Watts / 650 VA
Max Configurable Power (Watts)	390 Watts / 650 VA
Nominal Output Voltage	230V
Nominal Output Voltage	Standby
Waveform Type	Stepped approximation to a sinewave
Output Connections	(1) Schuko CEE 7 (Surge Protection) , (3) Schuko CEE 7 (Battery Backup)

Input

Nominal Input Voltage	230V
Input Frequency	45 - 65 Hz (auto sensing)
Input Connections	Schuko CEE 7/7P
Cord Length	1.16 meters
Input voltage range for main operations	180 - 266 V
Input voltage adjustable range for mains operation	160 - 278V
Maximum Input Current	3 A
Input Breaker Capacity	7 A

Batteries & Runtime

Battery Type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Included Battery Modules	0
Battery Slots Empty	0
Typical recharge time	8 hour(s)

Replacement Battery	APCRBC110
RBC Quantity	1

Communications & Management

Interface Port(s)	USB
Available SmartSlot®; Interface Quantity	0
Control panel	LED Status display with On Line : On Battery
Audible Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge energy rating	273 joules
---------------------	------------

Physical

Maximum Height	200.0 mm
Maximum Width	115.0 mm
Maximum Depth	256.0 mm
Rack Height	0 U
Net Weight	5.8 kg
Shipping Weight	6.6 kg
Shipping Height	344.0 mm
Shipping Width	200.0 mm
Shipping Depth	279.0 mm
Master Carton Units	0.0
Master Carton Weight	0.0 lbs
Color	Black
Units per Pallet	0.0

Environmental

Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 95 %
Operating Elevation	0-3000 meters
Storage Temperature	-15 - 40 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0-9000 meters
Audible noise at 1 meter from surface of unit	45.000 dB

Conformance

Approvals	EAC
Standard warranty	2 years repair or replace

Sustainable Offer Status

RoHS	Compliant
REACH	REACH: Contains No SVHCs