

APC Back-UPS (BX700UI)

700VA, 230V, AVR, 1 x IEC-320 C14 In, 4 x IEC 320 C13 Out



Price details:

Price excl. VAT: 68.45 €

Eco fees: 0.00 €

VAT 21 %: 14.37 €

Product details:

Product code: BX700UI

EAN: 0731304315803

Manufacturer: APC

PDF generated on: 9 March, 2017



82.82 €

* VAT included

USB connection

Use your PC to access additional power protection and management features for your UPS via a USB Port.

Telephone dataline surge protection

Provides protection of connected equipment from power surges traveling on telephone lines.

Automatic Voltage Regulation (AVR)

Automatically steps up low voltage and steps down high voltage to levels that are suitable for your equipment.

Main specifications:

Power

| | |
|--------------------------------|----------|
| Output power capacity: | 700 VA |
| Output power: | 390 W |
| Input operation voltage (min): | 140 V |
| Input operation voltage (max): | 300 V |
| Power supply input frequency: | 50/60 Hz |
| Surge energy rating: | 273 J |
| Efficiency: | 96.6 % |
| Output frequency regulation: | 50/60 Hz |

Ports & interfaces

| | |
|-------------------------------|-------------|
| AC outlets quantity: | 4 |
| AC outlet types: | C13 coupler |
| Cable length: | 1.22 m |
| USB port: | Y |
| Number of output IEC jumpers: | 1 |

Battery

| | |
|-----------------------------------|-------------------------|
| Battery technology: | Sealed Lead Acid (VRLA) |
| Number of batteries supported: | 1 |
| Battery recharge time: | 6 h |
| Typical backup time at half load: | 8.7 min |
| Typical backup time at full load: | 1.3 min |
| Replacement battery cartridge: | APCRBC110 |
| Automatic battery test: | Y |
| Battery replacement alarms: | LED |
| Battery capacity: | 7.2 Ah |
| Battery voltage: | 12 V |

| | |
|-------------------------------------|---|
| Battery life (max): | 5 year(s) |
| Battery capacity: | 81 VAh |
| Design | |
| Form factor: | Tower |
| Colour of product: | Black |
| Performance | |
| UPS topology: | Line-Interactive |
| Hold time (max): | 4 ms |
| Surge protection: | Y |
| Surge protection features: | Digital Subscriber Line (DSL),Fax,Modem |
| Waveform: | Sine |
| Automatic Voltage Regulation (AVR): | Y |
| Noise level: | 45 dB |
| LED indicators: | Y |
| Audible alarm(s): | Y |
| Audible alarm modes: | Low battery alarm,Overload alarm |
| Technical details | |
| Input connections: | IEC-320 C14 |
| Operational conditions | |
| Operating temperature (T-T): | 0 - 40 °C |
| Storage temperature (T-T): | -15 - 40 °C |
| Operating relative humidity (H-H): | 0 - 95 % |
| Storage relative humidity (H-H): | 0 - 95 % |
| Operating altitude: | 0 - 3000 m |
| Non-operating altitude: | 0 - 9000 m |
| Certificates | |
| Certification: | REACH |
| RoHS compliance: | Y |
| Weight & dimensions | |
| Width: | 115 mm |
| Depth: | 256 mm |
| Height: | 200 mm |
| Weight: | 6000 g |
| Package width: | 295 mm |
| Package depth: | 340 mm |
| Package height: | 275 mm |
| Package weight: | 6500 g |
| Packaging content | |
| Bundled software: | PowerChute Personal Edition |
| Manual: | Y |
| Other features | |
| Nominal output voltage: | 230 V |
| Nominal input voltage: | 230 V |

*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.